

---

**111. RESIDENTIAL DISTRICT (R11)**

---

This District provides for low-scale development in mature single family areas.

**111.1 Uses Permitted:**

- (1) Single family dwellings
- (2) Home occupations
- (3) Accessory buildings and uses
- (4) Group homes
- (5) Repealed. (B/L No. 13063-12-05-14)
- (6) Category A supportive housing facilities, subject to the following conditions:
  - (a) the use shall be included as part of a comprehensive development plan subject to the CD (Comprehensive Development) District; and
  - (b) each living unit shall have a minimum floor area of 27 m<sup>2</sup> (290.6 sq.ft.). (B/L No. 11153-00-11-06)

**111.2 Lot Area and Width:**

Each lot shall have an area of not less than 668.88 m<sup>2</sup> (7200 sq.ft.) and a width of not less than 18.28 m (60.0 ft.).

**111.3 Lot Coverage:**

Lot coverage shall not exceed 40 percent.

**111.4 Development Density:**

- (1) Gross Floor Area. The density of development for a principal building shall not exceed
  - (a) for a house that exists on October 1, 1994, the lesser of a floor area ratio of 0.60 or 371.6 m<sup>2</sup> (4000 sq.ft.);
  - (b) for a house that is constructed after October 1, 1994 with a height of 6.1 m (20 ft.) or less, the lesser of a floor area ratio of 0.60 or 371.6 m<sup>2</sup> (4000 sq.ft.);

- (c) for a house that is constructed after October 1, 1994 with a height greater than 6.1 m (20 ft.), the lesser of a floor area ratio of 0.60 or 325.15 m<sup>2</sup> (3500 sq.ft.);
- (2) Above Grade Floor Area. The gross floor area for all floors located above a cellar, basement, crawl space or ground surface shall not exceed
  - (a) for a house that exists on October 1, 1994, the lesser of 0.30 of the lot area or 185.8 m<sup>2</sup> (2000 sq.ft.);
  - (b) for a house that is constructed after October 1, 1994 with a height of 6.1 m (20 ft.) or less, the lesser of a 0.30 of the lot area or 185.8 m<sup>2</sup> (2000 sq.ft.);

and for a house that is constructed after October 1, 1994 with a height greater than 6.1 m (20 ft.), the gross floor area for all floors, excluding the floor of the cellar, shall not exceed the lesser of 209 m<sup>2</sup> (2250 sq.ft.) or 112 m<sup>2</sup> (1205.6 sq.ft.) plus 0.20 of lot area, but the gross floor area of the second floor above grade shall not exceed 74.32 m<sup>2</sup> (800 sq.ft.).

- (3) Garage or Carport. The floor area of a garage or carport attached to any part of the principal building shall be included as gross floor area and above grade floor area except where the lot does not have lane access.  
(B/L No. 10192-95-05-08)
- (4) Accessory Buildings. The total gross floor area for all accessory buildings on a lot shall not exceed 56 m<sup>2</sup> (602.8 sq.ft.), but where a garage or carport
  - (a) is detached from a principal building and is located within 9 m (29.5 ft.) of the rear lot line, or
  - (b) is attached to the principal building on a lot that does not have lane access
 a maximum of 42 m<sup>2</sup> (452.1 sq.ft.) shall not be included as gross floor area but all other floor areas used for off-street parking shall be included as gross floor area. (B/L No. 10192-95-05-08)

**111.5 Height of Principal Building:**

- (1) The height of a principal building with a gross floor area greater than 325.15 m<sup>2</sup> (3500 sq.ft.) shall not exceed 6.1 m (20 ft.);
- (2) The height of a principal building with a gross floor area of 325.15 m<sup>2</sup> (3500 sq.ft.) or less shall not exceed

- (a) 7.62 m (25 ft.) if the building has a sloping roof, and
  - (b) 6.7 m (22 ft.) if the building has a flat roof.
- (3) Subject to the applicable exceptions in section 6.4(3), building height shall be measured from the lower of the front or rear average elevations to the highest point of the structure unless an addition is proposed to a building that exists on October 1, 1994, in which case the height shall be measured from the lower of the front or rear average elevations to the highest point of the addition.

**111.6 Depth of Principal Building:**

The depth of a principal building shall not exceed the lesser of 45 percent of the lot depth or 16.76 m (55 ft.).

**111.7 Front Yard:**

A front yard shall be provided of not less than 7.5 m (24.6 ft.) in depth, and not less than the average front depth of the two adjacent lots on each side of the lot, subject to section 6.12 (2.1).

**111.8 Side Yards:**

- (1) Side yards not less than 1.83 m (6 ft.) in width shall be provided on each side of the building.
- (2) In the case of a corner lot, the side yard adjoining the flanking street shall not be less than 3.5 m (11.5 ft.).
- (3) The side yard setbacks for the second floor above grade
  - (a) shall not be less than 7 m (23 ft.) for the sum of both side yards, but this requirement shall not be applied so as to require an overall width of less than 9.8 m (32.2 ft.) for that second floor except where the lot has a width less than 12.19 m (40 ft.). (B/L No. 10192-95-05-08)
  - (b) shall not be less than 1.83 m (6 ft.) on each side.

**111.9 Rear Yard:**

A rear yard shall be provided of not less than 9 m (29.5 ft.) in depth.

**111.10 Off-Street Parking:**

- (1) Off-street parking shall be provided and maintained in accordance with Schedule VIII of this Bylaw.

- (2) Access for vehicles to all off-street parking spaces shall be provided from a lane abutting the lot except where there is no abutting lane or the Director Engineering is satisfied that access from a lane is not feasible because of an extreme grade, in which case the Chief Building Inspector may approve access from a street.

(B/L No. 10124-94-12-05)