

103. RESIDENTIAL DISTRICT (R3)

This District preserves the basic minimum density of development in the mature single family areas of the Municipality.

103.1 Uses Permitted:

- (1) Single family dwellings
- (2) Home occupations
- (3) Accessory buildings and uses
- (4) Repealed. (B/L No. 13063-12-05-14)
- (5) Group homes (B/L No. 10123-94-12-05)
- (6) Category A supportive housing facilities, subject to the following conditions:
 - (a) the use shall be included as part of a comprehensive development plan subject to the CD (Comprehensive Development) District; and
 - (b) each living unit shall have a minimum floor area of 27 m² (290.6 sq.ft.).
(B/L No. 11153-00-11-06)

103.2 Lot Area and Width:

- (1) R3 District. Each lot shall have an area of not less than 557.40 m² (6,000 sq.ft.) and a width of not less than 15.0 m (49.2 ft.).
- (2) R3a District. Each lot shall have an area of not less than 840 m² (9,041.9 sq.ft.) and a width of not less than 21 m (68.9 ft.). (B/L No. 11726-04-05-10)

103.3 Lot Coverage:

Lot coverage shall not exceed 40 percent.

103.4 Development Density. Gross Floor Area:

- (1) In an R3a District the gross floor area of all floors shall not exceed the floor area ratio of:
 - (a) 0.60 for lots having a width of 22.5 m (73.8 ft.) or more;
 - (b) 0.55 for lots having a width of less than 22.5 m (73.8 ft.) but equal to or more than 21.8 m (71.5 ft.);
 - (c) 0.50 for lots having a width of less than 21.8 m (71.5 ft.) but equal to or more than 21 m (68.9ft.).
(B/L No. 13983-19-03-25)
- (2) The gross floor area of all accessory buildings on a lot shall not exceed 56 m² (602.8 sq.ft.).
- (3) A maximum of 42 m² (452.1 sq.ft.) of a garage or carport shall not be included as gross floor area under subsection (1).
- (4) A cellar constructed in the R3 District shall not have a floor area, including a garage or carport that exceeds the floor area of the storey next above it. (B/L No. 13983-19-03-25)

103.5 Development Density. Above Grade Floor Area:

- (1) For a principal building that exists on December 16, 1991, the gross floor area for all floors located above a cellar, basement, crawl space or ground surface shall not exceed the greater of (B/L No. 11032-99-12-13)
 - (a) 0.20 of the lot area + 130 m² (1,399.4 sq.ft.), or
 - (b) 0.40 of the lot area.

- (2) For a principal building other than one that exists on December 16, 1991, the gross floor area for all floors, excluding the floor of a cellar, shall not exceed the greater of (B/L No. 11032-99-12-13)
 - (a) 0.20 of the lot area + 130 m² (1,399.4 sq.ft.), or
 - (b) 0.40 of the lot area.
- (3) Where a garage or carport is attached to the principal building, the floor area in excess of 42 m² (452.1 sq.ft.) shall be included as above grade floor area under subsections (1) and (2).
- (4) For a single family dwelling, other than one located in an R3a District, the floor area of a first storey located above a cellar shall not exceed the maximum floor area permitted under subsections (1) and (2) less 0.15 of the lot area. (B/L No. 13983-19-03-25)

103.6 Height of Principal Building:

- (1) The height of a principal building shall not exceed
 - (a) 2 1/2 storeys and 9.0 m (29.5 ft.) for a building with a sloping roof, or
 - (b) 2 1/2 storeys and 7.4 m (24.3 ft.) for a building with a flat roof
 as measured from the lower of the front average elevation or the rear average elevation to the highest point of the structure, subject to the applicable exceptions in section 6.4.
- (2) Notwithstanding subsection (1), for a principal building that exists on December 16, 1991, the height of any addition, measured from the lower of the front average elevation or the rear average elevation to the highest point of the addition, shall not exceed 9.0 m (29.5 ft.) if the building has a sloping roof or 7.4 m (24.3 ft.) if the building has a flat roof, subject to the applicable exceptions in section 6.4. (B/L No. 11032-99-12-13)

103.7 Depth of Principal Building:

The depth of a principal building shall not exceed the lesser of

- (a) 50 percent of the lot depth, or
- (b) 18.3 m (60.0 ft.)

103.8 Front Yard:

A front yard shall be provided of not less than 6.0 m (19.7 ft.) in depth, except that on a lot where the average front yard depth of the two adjacent lots on each side is more than the required front yard by at least 1.5 m (4.9 ft.), then the front yard shall be not less than that average, subject to section 6.12 (2.1).

103.9 Side Yards:

- (1) Side yards shall be provided on each side of the building of not less than 1.5 m (4.9 ft.) in width.
- (2) In the case of a corner lot, the side yard adjoining the flanking street shall be not less than 3.0 m (9.8 ft.) in width.

103.10 Rear Yard:

A rear yard shall be provided of not less than 7.5 m (24.6 ft.) in depth.

103.11 Off-Street Parking:

Off-street parking shall be provided and maintained in accordance with Schedule VIII of this Bylaw. (B/L No. 9663-91-12-16)